

Safety & Environmental Enforcement, Interior

§ 250.1007

substituted with the approval of the Regional Supervisor.

(6) Pipelines incoming to a subsea tie-in shall be equipped with a block valve and an FSV. Bidirectional pipelines connected to a subsea tie-in shall be equipped with only a block valve.

(7) Gas-lift or water-injection pipelines on unmanned platforms need only be equipped with an FSV installed immediately upstream of each casing annulus or the first inlet valve on the christmas tree.

(8) Bidirectional pipelines shall be equipped with a PSHL and an SDV immediately upon boarding each platform.

(9) Pipeline pumps must comply with section A7 of API RP 14C (as incorporated by reference in § 250.198). The setting levels for the PSHL devices are specified in paragraph (b)(3) of this section.

(c) If the required safety equipment is rendered ineffective or removed from service on pipelines which are continued in operation, an equivalent degree of safety shall be provided. The safety equipment shall be identified by the placement of a sign on the equipment stating that the equipment is rendered ineffective or removed from service.

If you have the pipeline out of service for:	Then you must:
(1) 1 year or less,	Isolate the pipeline with a blind flange or a closed block valve at each end of the pipeline.
(2) More than 1 year but less than 5 years,	Flush and fill the pipeline with inhibited seawater.
(3) 5 or more years,	Decommission the pipeline according to §§ 250.1750–250.1754.

§ 250.1007 What to include in applications.

(a) Applications to install a lease term pipeline or for a pipeline right-of-way grant must be submitted in quadruplicate to the Regional Supervisor. Right-of-way grant applications must include an identification of the operator of the pipeline. Each application must include the following:

(1) Plat(s) drawn to a scale specified by the Regional Supervisor showing major features and other pertinent data including area, lease, and block designations; water depths; route; length in Federal waters; width of right-of-way, if applicable; connecting facilities; size; product(s) to be transported with anticipated gravity or den-

§ 250.1005 Inspection requirements for DOI pipelines.

(a) Pipeline routes shall be inspected at time intervals and methods prescribed by the Regional Supervisor for indication of pipeline leakage. The results of these inspections shall be retained for at least 2 years and be made available to the Regional Supervisor upon request.

(b) When pipelines are protected by rectifiers or anodes for which the initial life expectancy of the cathodic protection system either cannot be calculated or calculations indicate a life expectancy of less than 20 years, such pipelines shall be inspected annually by taking measurements of pipe-to-electrolyte potential.

§ 250.1006 How must I decommission and take out of service a DOI pipeline?

(a) The requirements for decommissioning pipelines are listed in § 250.1750 through § 250.1754.

(b) The table in this section lists the requirements if you take a DOI pipeline out of service:

sity; burial depth; direction of flow; X–Y coordinates of key points; and the location of other pipelines that will be connected to or crossed by the proposed pipeline(s). The initial and terminal points of the pipeline and any continuation into State jurisdiction shall be accurately located even if the pipeline is to have an onshore terminal point. A plat(s) submitted for a pipeline right-of-way shall bear a signed certificate upon its face by the engineer who made the map that certifies that the right-of-way is accurately represented upon the map and that the design characteristics of the associated pipeline are in accordance with applicable regulations.